

Model		RTV-X900 General Purpose	RTV-X900 Worksite		RTV-X1120 General Purpose	RTV-X1120 Worksite		RTV-X1120 Deluxe		RTV-X1100C		RTV-X1140 Worksite		
Body color		Kubota Orange	Kubota Orange	Realtree® AP Camo	Kubota Orange	Kubota Orange	Realtree® AP Camo	Kubota Orange	Realtree® AP Camo	Kubota Orange	Realtree® AP Camo	Kubota Orange	Realtree® AP Camo	
Engine	Make	KUBOTA D902-E4-UV				KUBOTA D1105-E4-UV								
	Type	3-cylinders, 4-cycle, diesel, OHV				3-cylinders, 4-cycle, diesel, OHV								
	Displacement cu.in (cc)	54.8 (898)				68.5 (1123)								
	Horsepower HP (kW)/rpm	21.6 (16.1)@3200				24.8 (18.5)@3000								
	Cooling system	Liquid				Liquid								
Battery	560 CCA				670 CCA									
Transmission		Variable hydro transmission (VHT-X)												
Gear selection		Hi-Lo range forward, neutral, reverse												
Max. traveling speed mph (km/h)		0-25 (0-40)				0-29				0-25 (0-40)				
4WD system	Front differential	Limited-slip differential												
	Rear differential	Foot operated differential lock												
Steering		Hydrostatic power												
Brakes	Front / Rear	Wet-disc brakes												
	Parking brake	Rear wheel, hand operated												
Suspension	Front suspension	Independent, Dual A-arms with adjustable spring preload												
	Front in. (mm)	8 (205)												
	Rear suspension	Independent with coil over shock												
	Rear in. (mm)	8 (205)												
Ground clearance	Front in. (mm)					10.5 (266)				11.2 (285)				
	Rear in. (mm)					10.4 (263)				9.4 (240)				
Headlights		Two 37.5 Watt halogen				Two 37.5 Watt blue-tint				Two 37.5 Watt halogen				
Occupant Protective System (OPS)	ROPS structure in. (mm)	2.0 (50.8) steel tube				2.4 x 2.4 (61 x 61) Formed steel tube				2.0 (50.8) steel tube				
	Seat belts	2-point				3-point				2-point				
	Certification	SAE J2194 and O SHA 1928 ROPS				SAE J2194 and OSHA1928 ROPS and ANSI B71.9				SAE J2194 and OSHA 1928 ROPS				
Dimensions	Length in. (mm)	120.3 (3055)	122.5 (3110)	120.3 (3055)	122.5 (3110)				142.1 (3610)					
	Width in. (mm)					63.2 (1605)				65.4				
	Height, overall in. (mm)					79.5 (2020)				82.3				
	Front tread in. (mm)									48.8 (1240)				
	Rear tread in. (mm)									48.8 (1240)				
	Wheelbase in. (mm)					80.5 (2045)				98.2 (2495)				
	Turning radius ft. (m)					13.1 (4.0)								
Weight lbs. (kg)	1907 (865)	1973 (895)	1995 (905)	2061 (935)				2370 (1075)						
Towing capacity lbs. (kg)									1300 (590)					
Payload capacity lbs. (kg)	1664 (755)	1598 (725)	1510 (685)				1629 (739)							
Cargo bed	Material	Steel												
	Width x Length in. (mm)	57.7 (1465) x 40.5 (1030) x 11.2 (285)								Long: 57.7 (1465) x 51.1 (1300) x 11.2 (285) / Short: 57.7 (1465) x 26.0 (660) x 11.2 (285)				
	Volume cu. ft. (m ³)	15.2 (0.43)								Long: 19.1 (0.54) / Short: 9.9 (0.28)				
	Bed height in. (mm)	34.9 (887)								35.4 (900)				
	Cargo bed load lbs. (kg)	1102 (500)								Long: 1102 (500) / Short: 661 (300)				
Dumping system		Manual	Hydro power lift	Manual	Hydro power lift									
Fuel tank capacity U.S. gals ()	7.9 (30)													
Sound rating at operator's ear at max rpm dB. (A)		85				84				83				
Tires	Front and rear	ATV	25 x 10-12, 6-ply				Optional	25 x 10-12, 6-ply	Optional	25 x 10-12, 6-ply	Optional	25 x 10-12, 6-ply		
		HDWS	Optional				Optional	25 x 10-12, 4-ply	Optional	25 x 10-12, 4-ply		Optional		
Front guard design		Simple, center only	Center and bumper		Simple, center only	Center and bumper and lens						Center and bumper (Orange model) / Center, bumper and lens (Camo model)		
Alloy wheel (not available with Turf tire)		Opt.		Opt.		Opt.		Std.		Opt. or Std. (Orange model) / Opt. (Camo model)				
Hydraulic bed lift		Opt.	Std.		Opt.							Std.		
Spray-on bed liner		—		Opt.		—								Opt.