SB10/15 SERIES SNOW BLOWERS

18-59 HP | Cat. 1



Snow business.

Land Pride's SB10 and SB15 Series of Snow Blowers are available in 3 popular sizes. The two-stage system – auger and impeller – allows the units to move large amounts of snow in a short amount of time. The 3-point hitch is telescopic to couple as close as possible to the tractor. The chute rotation and chute deflector are controlled manually, electrically, or hydraulically.

- · Optional hardened cutting edge
- · Shear bolt driveline
- · Heavy-duty chute
- Choice of skid shoes
- · Telescoping 3-Point



Large 20" or 24" impeller allows snow to be moved quickly and efficiently.



Augers are 3/8" x 2-1/2" with 14" or 16" diameter, and are protected by a shear-bolt.

	Horsepower	18-32 HP	18-59 HP	30-59 HP
-	Telescoping Hitch	Cat. 1, Quick-Hitch Adaptable		Cat. 1, Quick- Hitch Adaptable
	Working Width (cm)	51" (130)	64" (163)	74" (188)
	Weight - lb (kg)	390 (177)	501 (227)	545 (247)
	Main Housing Material	12 Gauge		12 Gauge
	Side Plate Material	3/16"		3/16"
	Optional Cutting Edge	Bolt-on, Reversible & Replaceable Hardened Steel		Bolt-on, Reversible & Replaceable Hardened Steel
	Optional Skid Shoes (Choice of)	Outer: Bolt-on, Adjustable & Wear Plate: Bolt-on, Ha Replaceable and Reve Button Style: Adjustable & R		rdened, ersible
	Impeller	20" Diameter, 4 Blades		24" Diameter, 4 Blades
	Impeller Housing Depth	6"		8"
	Auger	1 - 14" Diameter, 3/8" x 2-1/2" Flighting		1 - 16" Diameter, 3/8" x 2-1/2" Flighting
	Auger Paddles	2	4	4
	Drive Chain	#60 Heavy		#60 Heavy
	Chute Opening at Base	8"		10"
	Chute Rotation	Sprocket Type; Manual, Electric or Hydraulic		Sprocket Type; Manual, Electric or Hydraulic
	Chute Deflector Operation	Manual, Electric or Hydraulic		Manual, Electric or Hydraulic
	Driveshaft Shear Bolt	Grade 5 - 1/4 x 20		Grade 5 - 1/4 x 20
	PTO Driveline	Cat. 2, Shear Bolt		Cat. 3 Heavy, Shear Bolt
	Colors			
	00.0.0			



